

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** GLOBOSTAR® GROUP

**Supplier's address:** GLOBOSTAR® GROUP, THESSALONIKIS 98, 60132 KATERINI KATERINI PIERIAS, EL

**Model identifier:** SKU: 60194

## Type of light source:

|                                                     |                        |                                 |     |
|-----------------------------------------------------|------------------------|---------------------------------|-----|
| Lighting technology used:                           | LED                    | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | WIRES - TERMINAL BLOCK |                                 |     |
| Mains or non-mains:                                 | MLS                    | Connected light source (CLS):   | No  |
| Colour-tuneable light source:                       | No                     | Envelope:                       | -   |
| High luminance light source:                        | No                     |                                 |     |
| Anti-glare shield:                                  | No                     | Dimmable:                       | No  |

## Product parameters

| Parameter | Value | Parameter | Value |
|-----------|-------|-----------|-------|
|-----------|-------|-----------|-------|

### General product parameters:

|                                                                                                                                                |                            |                                                                                                                                                            |                        |
|------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                  | 42                         | Energy efficiency class                                                                                                                                    | D                      |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 5 250 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 6 000                  |
| On-mode power ( $P_{on}$ ), expressed in W                                                                                                     | 41,6                       | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal                                                                               | 0,00                   |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal                                                | -                          | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 85                     |
| Outer dimensions without separate control gear, light-                                                                                         | Height                     | Spectral power distribution in the range 250 nm to 800 nm, at full-load                                                                                    | See image in last page |
|                                                                                                                                                | Width                      |                                                                                                                                                            |                        |
|                                                                                                                                                | Depth                      |                                                                                                                                                            |                        |

|                                                                                                                         |       |                                                                    |                |  |
|-------------------------------------------------------------------------------------------------------------------------|-------|--------------------------------------------------------------------|----------------|--|
| ing control parts and non-lighting control parts, if any (millimetre)                                                   |       |                                                                    |                |  |
| Claim of equivalent power <sup>(a)</sup>                                                                                | Yes   | If yes, equivalent power (W)                                       | 350            |  |
|                                                                                                                         |       | Chromaticity coordinates (x and y)                                 | 0,314<br>0,348 |  |
| <b>Parameters for directional light sources:</b>                                                                        |       |                                                                    |                |  |
| Peak luminous intensity (cd)                                                                                            | 1 500 | Beam angle in degrees, or the range of beam angles that can be set | 60             |  |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |       |                                                                    |                |  |
| R9 colour rendering index value                                                                                         | 6     | Survival factor                                                    | 0,90           |  |
| the lumen maintenance factor                                                                                            | 0,92  |                                                                    |                |  |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |       |                                                                    |                |  |
| displacement factor (cos $\phi_1$ )                                                                                     | 0,94  | Colour consistency in McAdam ellipses                              | 2              |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b)  | If yes then replacement claim (W)                                  | -              |  |
| Flicker metric (Pst LM)                                                                                                 | 0,0   | Stroboscopic effect metric (SVM)                                   | 0,0            |  |

(a) '-': not applicable;

(b) '-': not applicable;

