Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: GLOBOSTAR® GROUP

Supplier's address: GLOBOSTAR LED LIGHTING AND ACCESSORIES GROUP, 1st Km Old National Road Katerinis-Thessalonikis 1, 60100 KATERINI KATERINI PIERIAS, EL

Model identifier: SKU: 70601

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS				
Light source cap-type	WIRES						
(or other electric interface)							
Mains or non-mains:	NMLS	Connected light source (CLS):	No				
Colour-tuneable light source:	No	Envelope:	-				
High luminance light source:	No						
Anti-glare shield:	No	Dimmable:	Yes				
Product parameters							

Parameter		Value	Parameter	Value			
General product parameters:							
0,	nption in on- 00 h), rounded st integer	4	Energy efficiency class	G			
dicating if it refe a sphere (360 ^o)	s flux (фuse), in- ers to the flux in , in a wide cone nrrow cone (90º)	176 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	4 500			
On-mode power (P _{on}), ex- pressed in W		3,9	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00			
(P _{net}) for CLS,	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	70			
Outer dimen-	er dimen- Height 12 Spectral p		Spectral power dis-	See image			
sions without	Width	12	tribution in the	in last page			
separate con- trol gear, light-		1 000	range 250 nm to 800 nm, at full-load				

ing control parts and non- lighting con- trol parts, if							
any (millime- tre)							
Claim of equivalent power	^{a)} Ye	es If yes, o power (W)	equivalent	15			
		Chromatic	ity coordi-	0,380			
		nates (x ar	id y)	0,380			
Parameters for LED and OLED light sources:							
R9 colour rendering index	value 3	S Survival fa	ctor	0,90			
the lumen maintenance fac	ctor 0,9	90					
(2)	l.	l.					

(a)'-' : not applicable;

(b)_{'-'} : not applicable;



