Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: GLOBOSTAR® GROUP

Supplier's address: GLOBOSTAR LED LIGHTING AND ACCESSORIES GROUP, 1st Km Old National

Road Katerinis-Thessalonikis 1, 60100 KATERINI KATERINI PIERIAS, EL

Model	identifier:	SKU: 90754
-------	-------------	------------

Type of	light	source:
---------	-------	---------

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	WIRES		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

Product parameters

Product parameters				
Parameter		Value	Parameter	Value
General product parameters:				
· · · · · · · · · · · · · · · · · · ·	mption in on- 00 h), rounded st integer	14	Energy efficiency class	G
dicating if it refo a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	864 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	100010000
On-mode pow pressed in W	ver (P _{on}), ex-	14,4	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	60
Outer dimen-	Height	30	Spectral power dis-	See image
sions without	Width	20	tribution in the	in last page
separate con-	Depth	1 000		

trol gear, lighting control parts and non-lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load		
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	50	
		Chromaticity coordi-	0,247	
		nates (x and y)	0,004	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	-80	Survival factor	0,90	
the lumen maintenance factor	0,94			

(a)'-': not applicable; (b)'-': not applicable;

