Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: GLOBOSTAR® GROUP

Supplier's address: GLOBOSTAR LED LIGHTING AND ACCESSORIES GROUP, 1st Km Old National

Road Katerinis-Thessalonikis 1, 60100 KATERINI KATERINI PIERIAS, EL

Model identifier:	SKU: 90591
-------------------	------------

111	nn	Λt	IIαn	 · ^ · ·	rca
ıv	IJC.	.,,	וצוו	 	
- 7	~	•	o.	 	rce:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	WIRES		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
_ · · · · · · · · · · · · · · · · · · ·	mption in on- 00 h), rounded st integer	5	Energy efficiency class	G
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	280 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 500
On-mode pow pressed in W	ver (P _{on}), ex-	4,8	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, (tandby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82
Outer dimen- sions without	Height	2	Spectral power distribution in the	See image in last page
separate con- trol gear, light-	Width Depth	7 5 000	range 250 nm to 800 nm, at full-load	iii iast þage

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	15
		Chromaticity coordi-	0,380
		nates (x and y)	0,380
Parameters for LED and OLED light sources:			
R9 colour rendering index value	3	Survival factor	0,80
the lumen maintenance factor	0,80		

(a)'-': not applicable; (b)'-': not applicable;



