

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** GLOBOSTAR® GROUP

**Supplier's address:** GLOBOSTAR LED LIGHTING AND ACCESSORIES GROUP, 1st Km Old National Road Katerinis-Thessalonikis 1, 60100 KATERINI KATERINI PIERIAS, EL

**Model identifier:** SKU: 61692

## Type of light source:

|                                                     |                          |                                 |     |
|-----------------------------------------------------|--------------------------|---------------------------------|-----|
| Lighting technology used:                           | LED                      | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | WIRES-VDE TERMINAL BLOCK |                                 |     |
| Mains or non-mains:                                 | MLS                      | Connected light source (CLS):   | No  |
| Colour-tuneable light source:                       | No                       | Envelope:                       | -   |
| High luminance light source:                        | No                       |                                 |     |
| Anti-glare shield:                                  | No                       | Dimmable:                       | No  |

## Product parameters

| Parameter | Value | Parameter | Value |
|-----------|-------|-----------|-------|
|-----------|-------|-----------|-------|

### General product parameters:

|                                                                                                                                                |        |                          |                                                                                                                                                            |                        |
|------------------------------------------------------------------------------------------------------------------------------------------------|--------|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                  |        | 3                        | Energy efficiency class                                                                                                                                    | E                      |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |        | 300 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700                  |
| On-mode power ( $P_{on}$ ), expressed in W                                                                                                     |        | 3,0                      | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal                                                                               | 0,00                   |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal                                                |        | -                        | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 85                     |
| Outer dimensions without separate control gear, light-                                                                                         | Height | 220                      | Spectral power distribution in the range 250 nm to 800 nm, at full-load                                                                                    | See image in last page |
|                                                                                                                                                | Width  | 220                      |                                                                                                                                                            |                        |
|                                                                                                                                                | Depth  | 30                       |                                                                                                                                                            |                        |

|                                                                                                                         |      |                                                                    |                |  |
|-------------------------------------------------------------------------------------------------------------------------|------|--------------------------------------------------------------------|----------------|--|
| ing control parts and non-lighting control parts, if any (millimetre)                                                   |      |                                                                    |                |  |
| Claim of equivalent power <sup>(a)</sup>                                                                                | Yes  | If yes, equivalent power (W)                                       | 25             |  |
|                                                                                                                         |      | Chromaticity coordinates (x and y)                                 | 0,440<br>0,403 |  |
| <b>Parameters for directional light sources:</b>                                                                        |      |                                                                    |                |  |
| Peak luminous intensity (cd)                                                                                            | 130  | Beam angle in degrees, or the range of beam angles that can be set | 36             |  |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |      |                                                                    |                |  |
| R9 colour rendering index value                                                                                         | 9    | Survival factor                                                    | 0,94           |  |
| the lumen maintenance factor                                                                                            | 0,94 |                                                                    |                |  |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |      |                                                                    |                |  |
| displacement factor (cos $\phi_1$ )                                                                                     | 0,94 | Colour consistency in McAdam ellipses                              | 2              |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b) | If yes then replacement claim (W)                                  | -              |  |
| Flicker metric (Pst LM)                                                                                                 | 0,0  | Stroboscopic effect metric (SVM)                                   | 0,0            |  |

(a) '-': not applicable;

(b) '-': not applicable;

