

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: GLOBOSTAR® GROUP

Supplier's address: GLOBOSTAR LED LIGHTING AND ACCESSORIES GROUP, 1st Km Old National Road Katerinis-Thessalonikis 1, 60100 KATERINI KATERINI PIERIAS, EL

Model identifier: SKU: 60686

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type (or other electric interface)	WIRES - TERMINAL BLOCK		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------

General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	8	Energy efficiency class	E
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	800 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	8,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, light-	Height	80	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	80	
	Depth	35	
			See image in last page

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	70
		Chromaticity coordinates (x and y)	0,440 0,403
Parameters for directional light sources:			
Peak luminous intensity (cd)	150	Beam angle in degrees, or the range of beam angles that can be set	30
Parameters for LED and OLED light sources:			
R9 colour rendering index value	12	Survival factor	0,95
the lumen maintenance factor	0,92		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0,80	Colour consistency in McAdam ellipses	2
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	.. ^(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a)'.-' : not applicable;

(b)'.-' : not applicable;



EPREL registration number: 2300317

Model placed on the Union market from 01/06/2025.



<https://eprel.ec.europa.eu/qr/2300317>

Supplier: GLOBOSTAR GROUP SINGLE MEMBER S.A. (Im-
porter)

Website: www.globostar.gr

Customer care service:

Name: GLOBOSTAR LED LIGHTING AND ACCESSORIES G
ROUP

Website: www.globostar.gr

Email: eprel2021@globostar.eu

Phone: 00306980878477

Address:

1st Km Old National Road Katerinis-Thessalonikis 1
60100 KATERINI
Greece