



pro audio



Cseries C500T/C600T/C800T High-performance Ceiling Speaker

C500T/C600T/C800T series high-performance ceiling speaker, designed for a wide range of commercial applications, suitable for language, foreground & background music of retail stores, restaurants, hotels, etc. The simple and generous appearance design makes the loudspeaker visually integrated into the ceiling decoration, which is in line with the safety labeling of many escape systems around the world.

C500T/C600T/C800T系列高性能吸顶安装扬声器，采用复合边中低音单元和球顶高音同轴设计，适合零售店、餐厅、酒店等场所的前景、背景音乐播放和语言扩声。简约大方的外观设计使扬声器视觉上完全融入天花装饰中，该系列产品符合全球众多逃生系统安全标注。



MODEL	C500T	C600T	C800T
FREQUENCY RESPONSE(-3dB)	140Hz-18KHz	130Hz-20KHz	120Hz-18KHz
INPUT VOLTAGE	100V	100V	100V
RATED POWER	8Ω/7.5W/15/30W	8Ω/10W/20/40W	8Ω/12.5W/25/50W
SENSITIVITY	88dB 1watt/1 metre	89dB 1watt/1 metre	90dB 1watt/1 metre
MAXIMUM SPL	93dB continuous,98dB peak	94dB continuous,99dB peak	95dB continuous,100dB peak
IMPEDANCE	8 ohms nominal	8 ohms nominal	8 ohms nominal
DISPERSION(-6dB)	90°	90°	90°
PACKAGE SIZE	525mm×490mm×400mm (8pcs/carton)	815mm×560mm×210m (6pcs/carton)	625mm×330mm×470mm (4pcs/carton)
NET WEIGHT	13.6kg/8pcs	12.72kg/6pcs	11.4kg/4pcs
GROSS WEIGHT	19.1kg/8pcs	18.48kg/6pcs	16.1kg/4pcs